

ALPHA SUPPORT PHONE (909) 307-2320

1. TECHNICAL SPECIFICATIONS

Protection index: IP20 The motor can be compatible with 15 remotes at most Received frequency: 433.92MHz Charging: 16.8V/1A Code: Rolling Charge time: 6 hours

Programming button

2. CHARGING AND WAKING UP MOTOR




Please charge the motor using charger 16.8V/1A before operation. The motor won't function until it has been charged.

Waking the motor up for the first time:

Method A Plug ALDC charger into charging port for a few seconds till motor vibrates.

Method B Press and hold white motor head button for 6 seconds, green LED will flash 3 times and then turn red.

3. CODE LEARNING



Press the button on the head for

1 second, the motor will vibrate.





Press UP and DOWN together and release.







The remote should now control the motor.

4. CHANGING THE RUNNING DIRECTION

Method A.



Long press for 5 seconds

Press motorhead's button for about 5 seconds until the motor vibrates.

Method B.



simultaneously.

Press UP and DOWN buttons

➡ ×6 🖙

Press the STOP button 6 times within 10s.



Press the DOWN button once

within 10s, the motor will vibrate.

×1



The motor's running direction is reversed.

The motor's running direction is reversed.

5. TURN ON STEP BY STEP FUNCTION The motor will move in small increments unless the button is held down.


Note: If the motor is in step-by-step mode, pressing the UP or DOWN button for 3s will make the motor will run continuously.












Press UP and DOWN buttons simultaneously.

Press the STOP button 2 times within 10s.

Press the UP button once within 10s, the motor will vibrate.

The motor will run step by step.

	X





Charging port



ALPHA SUPPORT PHONE (909) 307-2320

6. TURN OFF STEP BY STEP FUNCTION The motor will operate normally.

Note: If the motor is in step-by-step mode, pressing the UP or DOWN button for 3s will make the motor will run continuously.





Press UP and DOWN buttons simultaneously.





First, move the blind to the desired position.

First, move the blind to the desired position.

Press the DOWN button once within 10s, the motor will vibrate.

_

The motor will run continuously.

7. TOP LIMIT SETTING

First, move the blind to the desired position.




simultaneously.



Press the STOP button 2 times within 10s.



Press the UP button once within 10s, the motor will vibrate.



The TOP limit is set

8. BOTTOM LIMIT SETTING

Press UP and DOWN buttons

First, move the blind to the desired position.






Press the STOP button



Press the DOWN button once within 10s, the motor will vibrate.



The BOTTOM limit is set

Press UP and DOWN buttons simultaneously.










Press UP and DOWN buttons simultaneously.

Press the STOP button 4 times within 10s.

x 4⊫



Press the UP button once within 10s, the motor will vibrate.



The top limit is deleted.

10. BOTTOM LIMIT DELETING

First, move the blind to the desired position.








First, move the blind to the desired position.





Press UP and DOWN buttons simultaneously.

Press the STOP button 4 times within 10s.

Press the DOWN button once within 10s, the motor will vibrate.

The bottom limit is deleted.



ALPHA SUPPORT PHONE (909) 307-2320

11. CODE DELETING


Method A: This method deletes all channels from the remote you are holding from the motor.



Press the UP and DOWN

buttons simultaneously.







×1⊫

Press the UP button once within 10s, the motor will vibrate.

Method B: This method deletes all channels from all remotes from the motor's memory.





Press UP and DOWN buttons simultaneously.

Press the STOP button

6 times within 10s.



Press the UP button once within 10s, the motor will vibrate.



All channels from the remote you are holding are now deleted from this motor. Others will remain.



All the remote channels in the motor's memory are deleted.

12. ASSIGNING AN ADDITIONAL REMOTE





Press STOP 8 times, the motor will vibrate.

	×1⊑
•	
	×1⊑



NFW

Press STOP once and the motor will vibrate. The new remote channel will now operate the motor.

EXISTING Press UP and DOWN together and release on the existing remote.

EXISTING




13. THE THIRD LIMIT

First, move the blind to the desired position.

First, move the blind to the desired position.

A. Set the Third Limit

Note: The third limit is also named as the intermediate limit, it is available at any position between up and down limit. The third limit will be deleted automatically if the up or down limit is deleted.



Move the blind to the desired position and press STOP 4 times.



The motor will vibrate; it means the current position is set as the third limit.



「」 press for 2 seconds

Press the STOP button for 2s, the motor will run to the third limit position from any other current position.

B. Reset the Third Limit

The third limit will be deleted automatically if the up or down limit is deleted.




Move the blind to the desired position and press STOP 4 times.



The motor will vibrate; it means the current position is set as the third limit.



Press the STOP button for 2s, the motor will run to the third limit position from any other current position.





NFW

Press UP and DOWN together and release on the new remote.





ALPHA SUPPORT PHONE (909) <u>307-2320</u>

14. THE LIGHT INDICATOR

(1) Recharging Light Indicator

Red light

(1) When the battery is recharging, the red light is on.


Green Light

(2) When the battery is fully charged, the light will turn green.

Note: During motor charging, if red and green lights are both on, it means the charging source is under powered, please change the charging source.

(2) Low battery light indicator on motor





Red light flashing

1) When battery voltage is too low, press any button on the remote, motor will vibrate once and the red light on the motor will flash and motor will stop running, this situation lasts 10 times, please recharge now.

2) If the motor is not charged, the motor won't vibrate and only the red light will flash, the battery needs to be charged immediately.

15. SLEEP MODE

Put motor into "sleep mode". This function reboots the motor if you cannot assign a remote to the motor for the first time.

Press motor head button once, motor vibrates.

Press motor head button 4 times, red light illuminates with each press and then turns green.

⚠ Announcement

To ensure your safety and the continued safe operation of our products, we urge you to adhere to the following guidelines with regards to Lithium-Ion batteries:

1. **Avoid Overcharging** Overcharging the batteries can lead to overheating and, in extreme cases, fire. Once the motor's green light indicates a full charge, immediately disconnect it from the charging circuit to prevent overcharging.

2. **Prevent Overheating** Excessive heat can also pose a risk to the batteries. Please ensure that the motor is not exposed to prolonged periods of high temperature or direct sunlight, as this can lead to overheating and potential fire hazard.

3. **Immediate Action** In the event of any unusual warmth, discolouration, or odour emanating from the motor, immediately disconnect it from the power source and refrain from further use.

PLEASE NOTE:

- To keep product in good condition, please charge the motor every 3 months.
- Please do not let children play with the remote or motor.
- Storage temperature: -4°F to 149°F

Alpha Tubular Motors LLC 1840 S Commercenter Circle San Bernardino CA 92408



sales@alphamotors.us www.alphamotors.us T (909) 307-2320